


# N3PT035MP330K

## 3300 V 35 mΩ Silicon Carbide MOSFET

$V_{DS}$	$I_D$	$R_{DS(on)}$	Package
3300 V	88 A	35 mΩ	TO-247-4



(1) (2) (3) (4)

### Features

- State-of-the-art SiC MOSFET technology
- Reliable gate oxide process
- Ultra-low output capacitance
- Best-in-class figure-of-merits,  $[R_{on} \cdot C_{oss}]$  and  $[R_{on} \cdot C_{rss}]$
- Stable switching characteristics up to 175 °C

### Benefits

- Higher system efficiency
- Reduced cooling requirements
- Increased power density
- Increased system switching frequency
- Enhanced system reliability
- Reduced total harmonic distortion

### Maximum Ratings

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit	Note
<b>Drain-Source Voltage</b>	$V_{(BR)DSS}$	$T_C = 25\text{ °C}$	3300	-	-	V	
<b>Gate-Source Voltage</b>	$V_{GS(max)}$		-10	-	25	V	
	$V_{GS,op}$	Recommended Operation	-	-5/+20	-		
<b>Continuous Drain Current</b>	$I_D$	$V_{GS} = 20\text{ V}, T_C = 25\text{ °C}$	-	-	88	A	Fig. 13
		$V_{GS} = 20\text{ V}, T_C = 100\text{ °C}$	-	-	63		
<b>Pulsed Drain Current</b>	$I_{D(pulse)}$	$T_C = 25\text{ °C}$	-	-	240	A	Fig. 12
<b>Power Dissipation</b>	$P_{tot}$	$T_C = 25\text{ °C}$	-	-	789	W	Fig. 14
<b>Operating and Storage Temperature</b>	$T_J, T_{stg}$		-55	-	175	°C	

### Applications

- Utility-scale renewable/ESS/HVDC interfaces, modular multi-level converters, SSTs, DC-as-a-Service
- Defense/Maritime medium voltage converters & Directed Energy/Pulse Power
- Industrial medium voltage drives & VFDs
- Data-Center/AI Infrastructure (UPS, SST, rectifier, and protection -stages)
- Medium voltage medical imaging & therapy

## Thermal and Package Characteristics

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit	Note
<b>Thermal Resistance, Junction to Case</b>	$R_{thJC}$		-	0.13	0.62	°C/W	Fig. 11
<b>Thermal Resistance, Junction to Ambient</b>	$R_{thJA}$		-	-	40	°C/W	
<b>Weight</b>	$W_T$		-	6.6	-	g	
<b>Solder Temperature</b>	$T_L$	JEDEC J-STD-020	-	-	225	°C	
<b>Mounting Torque</b>	$T_M$	M3 or 6-32 screw	-	0.9	-	Nm	

## Electrical Characteristics ( $T_c = 25\text{ °C}$ unless otherwise specified)

### STATIC CHARACTERISTICS

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit	Note
<b>Drain-Source Breakdown Voltage</b>	$V_{(BR)DSS}$	$V_{GS} = 0\text{ V}, I_D = 100\text{ }\mu\text{A}$	3300	-	-	V	
<b>Zero Gate Voltage Drain Current</b>	$I_{DSS}$	$V_{DS} = 0\text{ V}, V_{GS} = 0\text{ V}$	-	1	100	$\mu\text{A}$	
<b>Gate Threshold Voltage</b>	$V_{GS(th)}$	$V_{GS} = V_{DS}, I_D = 10\text{ mA}$	1.8	2.6	3	V	
<b>Gate-Source Leakage Current</b>	$I_{GSS}$	$V_{GS} = -10 / +25\text{ V}, V_{DS} = 0\text{ V}$	-	-	$\pm 100$	nA	
<b>Transconductance</b>	$g_{fs}$	$V_{DS} = 10\text{ V}, I_D = 40\text{ A}$	-	20.2	-	S	Fig. 8
<b>Drain-Source On-State Resistance</b>	$R_{DS(on)}$	$V_{GS} = 20\text{ V}, I_D = 40\text{ A}$	-	33	40	mΩ	Fig. 1
		$V_{GS} = 20\text{ V}, I_D = 40\text{ A}, T_C = 175\text{ °C}$	-	101	-	mΩ	Fig. 3
		$V_{GS} = 18\text{ V}, I_D = 40\text{ A}$	-	35	-	mΩ	Fig. 1
		$V_{GS} = 18\text{ V}, I_D = 40\text{ A}, T_C = 175\text{ °C}$	-	102	-	mΩ	Fig. 3

## DYNAMIC CHARACTERISTICS

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit	Note
<b>Input Capacitance</b>	$C_{iss}$	$V_{GS} = 0 \text{ V}, V_{DS} = 1700 \text{ V}, V_{AC} = 25 \text{ mV}, f = 100 \text{ kHz}$	-	8630	-	pF	Fig. 10
<b>Output Capacitance</b>	$C_{oss}$		-	120	-		
<b>Reverse Capacitance</b>	$C_{rss}$		-	13.8	-		
<b>Gate-Source Charge</b>	$Q_{GS}$	$V_{DS} = 1000 \text{ V}, V_{GS} = -5 / +20 \text{ V}, I_D = 40 \text{ A}$	-	81	-	nC	Fig. 15
<b>Gate-Drain Charge</b>	$Q_{GD}$		-	76	-		
<b>Total Gate Charge</b>	$Q_G$		-	482	-		
<b>Internal Gate Resistance</b>	$R_{G(int)}$	$V_{AC} = 25 \text{ mV}, f = 1 \text{ MHz}$	-	2.4	-	Ω	
<b>Turn-On Switching Energy</b>	$E_{ON}$	$V_{DD} = 1700 \text{ V}, I_D = 40 \text{ A}, V_{GS} = -5 / +20 \text{ V}, R_{G(ext)} = 5 \text{ } \Omega, L = 500 \text{ } \mu\text{H}$	-	2999	-	μJ	Fig. 16 Fig. 17 Fig. 18
<b>Turn-Off Switching Energy</b>	$E_{OFF}$		-	712	-		
<b>Total Switching Energy</b>	$E_{TOT}$		-	3711	-		
<b>Turn-On Delay Time</b>	$t_{d(on)}$	$V_{DD} = 1700 \text{ V}, I_D = 40 \text{ A}, V_{GS} = -5 / +20 \text{ V}, R_{G(ext)} = 5 \text{ } \Omega, L = 500 \text{ } \mu\text{H}$ Timing relative to $V_{DS}$ Inductive Load	-	31	-	ns	Fig. 19
<b>Rise Time</b>	$t_r$		-	48	-		
<b>Turn-Off Delay Time</b>	$t_{d(off)}$		-	111	-		
<b>Fall Time</b>	$t_f$		-	25	-		

## BODY DIODE CHARACTERISTICS

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit	Note
<b>Diode Forward Voltage</b>	$V_{SD}$	$V_{GS} = -5 \text{ V}, I_{SD} = 40 \text{ A}$	-	5.3	-	V	Fig. 20
		$V_{GS} = -5 \text{ V}, I_{SD} = 40 \text{ A}, T_J = 175 \text{ } ^\circ\text{C}$	-	4.5	-	V	Fig. 21
<b>Continuous Diode Forward Current</b>	$I_S$	$V_{GS} = -5 \text{ V}$	-	104	-	A	
<b>Reverse Recovery Time</b>	$t_{rr}$	$V_R = 1700 \text{ V}, I_{SD} = 40 \text{ A}, V_{GS} = -5 \text{ V}, diF/dt = 2500 \text{ A}/\mu\text{s}$	-	22	-	ns	
<b>Reverse Recovery Charge</b>	$Q_{rr}$		-	544	-	nC	
<b>Peak Reverse Recovery Current</b>	$I_{RRM}$		-	38	-	A	

**Typical Performance**




Figure 1: Output Characteristics at 25 °C




Figure 2: Output Characteristics at 125 °C




Figure 3: Output Characteristics at 175 °C




Figure 4: On-Resistance vs. Temperature




Figure 5: On-Resistance vs. Drain Current




Figure 6: On-Resistance vs. Gate Voltage

**Typical Performance**




Figure 7: Normalized On-Resistance vs. Temperature




Figure 8: Transfer Characteristics




Figure 9: Threshold Voltage vs. Temperature




Figure 10: Capacitances vs. Drain-Source Voltage (0-1000 V)




Figure 11: Transient Thermal Impedance

**Typical Performance**




Figure 12: Safe Operating Area




Figure 13: Current De-rating Curve




Figure 14: Power De-rating Curve




Figure 15: Gate Charge Characteristics




Figure 16: Inductive Switching Energy vs. Drain Current ( $V_{DD} = 1700\text{ V}$ )




Figure 17: Inductive Switching Energy vs.  $R_{G(ext)}$  ( $V_{DD} = 1700\text{ V}$ )

**Typical Performance**




Figure 18: Inductive Switching Energy vs. Temperature (V<sub>DD</sub> = 1700 V)




Figure 19: Switching Times vs. R<sub>G(ext)</sub> (V<sub>DD</sub> = 1700 V)




Figure 20: Body Diode Characteristics at 25 °C




Figure 21: Body Diode Characteristics at 175 °C

**Dynamic Testing Circuit Schematics**




Figure 22: Inductive Load Switching Test Circuit




Figure 23: Inductive Load Switching Test Waveforms




Figure 24: Reverse Recovery Test Circuit




Figure 25: Body Diode Reverse Recovery Test Waveforms




Figure 26: Gate Charge Test Circuit





Figure 27: Gate Charge Test Waveforms

**Package Dimensions**



**NOTES:**

1. DIMENSIONS ARE IN MILLIMETERS
2. DIMENSION D & E DO NOT INCLUDE MOLD FLASH, MOLD FLASH SHALL NOT EXCEED 0.127 MM PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTERMOST EXTREME OF THE PLASTIC BODY.
3.  $\phi P$  TO HAVE A MAXIMUM DRAFT ANGLE OF 1.5° TO THE TOP OF THE PART WITH A MAXIMUM HOLE DIAMETER OF 3.65mm.
4. EJECTION MARK DEPTH 0.10<sup>+0.15</sup>/<sub>0.08</sub>

AREA	MIN	NOM	MAX
A	4.83	5.02	5.21
A1	2.29	2.415	2.54
A2	1.86	1.99	2.12
D	23.30	23.45	23.60
D1	15.85	16.55	17.25
D2	1.02	1.17	1.32
E	15.75	15.94	16.13
E1	13.89	14.02	14.15
E2	3.68	4.39	5.10
E3	1.00	1.45	1.90
E4	12.38	12.91	13.43
e	2.540 BSC		
e1	5.080 BSC		
L	17.31	17.57	17.82
L1	3.97	4.17	4.37
L2	2.35	2.50	2.65
b	1.07	-	1.33
b1	1.07	1.20	1.28
b2	2.39	-	2.64
b3	2.39	-	2.69
b4	2.39	-	2.94
b5	2.39	2.53	2.84
b6	1.07	-	1.60
b7	1.30	-	1.70
c	0.55	-	0.68
c1	0.55	0.60	0.65
$\phi P$	3.51	3.58	3.65
Q	5.49	5.75	6.00
S	6.04	6.15	6.30
$\phi P1$	7.18 REF		
T	17.5° REF		
W	3.5° REF		
X	4° REF		

## Warranty & Disclaimers

Since NoMIS Power does not control the use of its products, there are no express warranties that extend beyond the description herein.

THIS PRODUCT IS PROVIDED "AS IS". NOMIS POWER MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE PRODUCT INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE. IN NO EVENT WILL NOMIS POWER BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, OR CONSEQUENTIAL LOSS, DAMAGE, COST, OR EXPENSE OF ANY KIND WHATSOEVER (INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS OF PROFIT, BUSINESS INTERRUPTION, OR LOSS OF INFORMATION) RELATED TO THE USE OF, OR INABILITY TO USE, THE PRODUCT, HOWEVER CAUSED, EVEN IF NOMIS POWER HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, NOMIS POWER'S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE PRODUCT OR ITS USE, OR INABILITY TO USE, WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO THE SELLER FOR THE PRODUCT.

NoMIS Power's products are not recommended or authorized for usage in equipment or applications that require extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury, such as life support or medical instruments or applications. Buyers assume all risk and liability for using our products in such applications and agree to defend, indemnify and hold harmless NoMIS Power from any and all damages, claims, suits or expenses resulting from such use.

NoMIS Power further does not warrant the accuracy or completeness of the information, text, graphics, links or other items contained in this Data Sheet. This Data Sheet and the information herein may be used only with NoMIS Power products, including to design, test, and integrate NoMIS Power products with your application. Use of this information in any other manner violates these terms. Information regarding device application is provided only for your convenience and may be superseded by updates at any time. It is your responsibility to ensure that your application meets with your specifications.

NoMIS Power may make changes to this Data Sheet at any time, or to the product described herein, at any time without notice.

No licenses are conveyed, implicitly or otherwise, under any NoMIS Power intellectual property rights.

NoMIS Power and  **NoMIS Power** are trademarks of NoMIS Power Corporation in the United States and/or other countries. NoMIS Power reserves the right to make changes without further notice to any products herein. NoMIS Power makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does NoMIS Power assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. NoMIS Power does not convey any license under its patent rights nor the rights of others.

**NoMIS Power Corporation**

251 Fuller Rd, Albany, NY 12203, USA

together@NoMISPower.com | NoMISPower.com